

Product Description

The BR115 is a High Performance Subwoofer in Bass Reflex Configuration. It contains one 15" Cone Driver with High Temperature 4" Voicecoil and Ferrite Magnet.

A large ventilation port ensures high output and low noise.

A M20 Polemount makes combined Applications with G-ACOUSTIC Mid-High Speakers possible.

The BR115 has 4 rubber feet in symmetrical alignment which allows stable stacking also in Cardioid Applications.



Technical Data

| | |
|--|--|
| Description: | High Performance Subwoofer |
| Transducers: | 1x 15" , Bassreflex Loaded High Temperature Voicecoil |
| Frequency Range (-10dB) ¹ : | 34Hz - 300Hz |
| Sensitivity (1W/1m): | 98dB |
| Power Handling RMS ² : | 1000W |
| Maximum SPL ³ : | 138dB |
| Nominal Impedance: | 8Ω |
| Coverage (-6dB): | omnidirectional |
| Connectivity: | 2x SPEAKON NL4 type |
| Rigging: | only for ground applications |
| Dimensions (WxDxH): | 550mm x 620mm x 505mm |
| Weight: | 42kg |

¹ with G-ACOUSTIC processor setup in fullrange mode

² with G-ACOUSTIC processor setup, pink noise signal with 12dB crest factor

³ calculated SPL with 10ms burst signal at peak power (12dB above RMS power)

