

Product Description

The BR221 is a High Performance Subwoofer in Bass Reflex configuration. It contains two 21" Cone Drivers with High Temperature 4.5" Voicecoils and Ferrite Magnets.

Large Ventilation Ports ensures high output and low noise. A customized "flat edged" Basket allows cabinet dimensions, which are identical to conventional 18" designs.

The BR221 can be assigned with a Rigging Kit allowing to hang up to 8 Cabinets according to German DGUV17/18 Specification.

4 rubber feet in symmetrical alignment allow stable stacking also in cardioid applications.



Technical Data

| | |
|--|---|
| Description: | High Performance Subwoofer |
| Transducers: | 2x 21" , Bassreflex Loaded 4.5" High Temperature Voicecoil |
| Frequency Range (-10dB) ¹ : | 27Hz - 300Hz |
| Sensitivity (1W/1m): | 102dB |
| Power Handling RMS ² : | 3600W |
| Maximum SPL ³ : | 148dB |
| Nominal Impedance: | 4Ω |
| Coverage (-6dB): | omnidirectional |
| Connectivity: | 2x SPEAKON NL4 type |
| Rigging: | Rigging Kit for up to 8 BR221 |
| Dimensions (WxDxH): | 1270mm x 870mm x 560mm |
| Weight: | 108kg |

¹ with G-ACOUSTIC processor setup in fullrange mode

² with G-ACOUSTIC processor setup, pink noise signal with 12dB crest factor

³ calculated SPL with 10ms burst signal at peak power (12dB above RMS power)

