

Product Description

The G15 is a Professional 15" High Performance Loudspeaker, arranged as 2-way Configuration with Bassreflex Loading. The Cabinet consists of a 15" driver with 75mm (3") Voicecoil and Ferrite Magnet as Low Frequency Transducer, together with a 75mm (3") High Frequency Ferrite Compression Driver with 1.4" exit, mounted on a 70° x 50° Constant Directivity Horn.

For Rigging and Mounting are various M8 Points available, on top and back in 100mm distance to use Standard Mounting Accessories for Ceiling, Wall and Standing application.

The G15 can be applied together with any G-ACOUSTIC Subwoofer to increase Output and Low Frequency Extension.



Technical Data

Description:	2-way Passive Speaker
Transducers:	LF: 1x 15" , Bassreflex Loaded
	HF: 1x 3" Diaphragm Compression Driver
Frequency Range (-10dB) ¹ :	43Hz - 19kHz
Sensitivity (1W/1m):	98dB
Power Handling RMS ² :	700W
Nominal Impedance:	8Ω
Coverage (-6dB):	70° x 50°
Connectivity:	2x SPEAKON NL4 type
Rigging:	10x M8 rigging points
Dimensions (WxDxH):	430mm x 430mm x 705mm
Weight:	24kg

¹ with G-ACOUSTIC processor setup in fullrange mode

² with G-ACOUSTIC processor setup, pink noise signal with 12dB crest factor

