

## Product Description

The K12 is a Professional 12" Loudspeaker, arranged as 2-Way Configuration with backwards Bassreflex Loading. The Cabinet consists of a 12" driver with 76mm (3") voicecoil and ferrite magnet as Low Frequency Transducer, together with a 46mm (1.75") High Frequency Compression Driver with 1" exit mounted on a rotatable 60°x40° Constant Coverage Horn.

For Rigging and Mounting are various M8 Points available, on top and back in 100mm distance to use Standard Mounting Accessories for Ceiling, Wall and Standing Application.

The K12 can be applied together with any G-ACOUSTIC Subwoofer to increase Output and Low Frequency Extension.



## Technical Data

Description:	2-way Passive Speaker
Transducers:	LF: 1x 12" , Bassreflex Loaded HF: 1x 1.75" Diaphragm Compression Driver
Frequency Range (-10dB) <sup>1</sup> :	45Hz - 20kHz
Sensitivity (1W/1m):	98dB
Power Handling RMS <sup>2</sup> :	450W
Nominal Impedance:	8Ω
Coverage (-6dB):	60°x40°
Connectivity:	2x SPEAKON NL4 type
Rigging:	M8 rigging points
Dimensions (WxDxH):	350mm x 380mm x 600mm
Weight:	22kg

<sup>1</sup> with G-ACOUSTIC processor setup in fullrange mode

<sup>2</sup> with G-ACOUSTIC processor setup, pink noise signal with 12dB crest factor

