

Product Description

The LAS5 Line Array Stick is a Professional High Power Column Array Loudspeaker, arranged as Biamp driven 2-way System in Closed Alignment. The cabinet consists of six 5" drivers with 44mm (1.75") Voicecoil and Ferrite Magnet as Low Frequency Transducers, together with two 44mm (1.75") High Frequency Compression Drivers with 1" exit and Neodymium Magnet, attached to a Line Source Waveguide with Constant Coverage horn. For mounting are various M8 points available, paired in 100mm distance to use standard Mounting Accessories for ceiling, wall and standing application.



Technical Data

Description:	2-way Biamp Column Speaker
Transducers:	LF: 6x 5" , Closed Alignment HF: 2x 1.75" Diaphragm Compression Driver
Frequency Range (-10dB) ¹ :	53Hz - 20kHz
Sensitivity (1W/1m):	99dB
Power Handling RMS ² :	600W
Maximum SPL ³ :	139dB
Nominal Impedance:	5Ω
Coverage (-6dB):	90°(H) x 25°(V)
Connectivity:	2x SPEAKON NL4 type, back/bottom
Rigging:	6x M8 rigging points
Dimensions (WxDxH):	150mm x 235mm x 1100mm
Weight:	24kg

¹ with G-ACOUSTIC processor setup in fullrange mode

² with G-ACOUSTIC processor setup, pink noise signal with 12dB crest factor

³ calculated SPL with 10ms burst signal at peak power (12dB above RMS power)

