

Product Description

The BR221 is a High Performance Subwoofer in Bass Reflex configuration. It contains two 21" Cone Drivers with High Temperature 4.5" Voicecoils and Ferrite Magnets.

Large Ventilation Ports ensures high output and low noise. A customized "flat edged" Basket allows cabinet dimensions, which are identical to conventional 18" designs.

The BR221 can be assigned with a Rigging Kit allowing to hang up to 8 Cabinets according to German DGUV17/18 Specification.

4 rubber feets in symmetrical alignment allow stable stacking also in cardioid applications.



Technical Data

Description:	High Performance Subwoofer
Transducers:	2x 21" , Bassreflex Loaded 4.5" High Temperature Voicecoil
Frequency Range (-10dB) ¹ :	27Hz - 300Hz
Sensitivity (1W/1m):	102dB
Power Handling RMS ² :	3600W
Maximum SPL ³ :	148dB
Nominal Impedance:	4Ω
Coverage (-6dB):	omnidirectional
Connectivity:	2x SPEAKON NL4 type
Rigging:	Rigging Kit for up to 8 BR221
Dimensions (WxDxH):	1150mm x 820mm x 600mm
Weight:	108kg

¹ with G-ACOUSTIC processor setup in fullrange mode

² with G-ACOUSTIC processor setup, pink noise signal with 12dB crest factor

³ calculated SPL with 10ms burst signal at peak power (12dB above RMS power)

